

Tiandy



TC-H363U Spec:W/4G/U/SE/4mm/V4.0

PT Camera

Wireless Series



KEY FEATURES

- Plastic Housing
- Up to 2304x1296@15fps
- S+265/H.265
- Built-in Mic & Speaker
- Operating Conditions -10°~50°, 0~95% RH
- Red and blue indicator lights
- IP65



Tiandy Technologies Co.,Ltd.

Email: sales@tiandy.com
Website: en.tiandy.com

Tel: +86-22-58596065
Fax: +86-22-58596048

SPECIFICATIONS

Camera	
Image Sensor	1/2.9"CMOS
Min. Illumination	Color:0.005Lux@(F1.6,AGC ON),B/W:0Lux with IR
Shutter Time	1s~1/100000s
Day&Night	N/A
WDR	DWDR
S/N	>50dB
Angle Adjustment	(P)Fixde Lens:-60°~60°;Pan & Tilt Lens:0~345° (T)Fixde Lens:5°-15°;Pan & Tilt Lens:-15~90° (R)Fixde Lens:0°;Pan & Tilt Lens:0°
Lens	
Lens Type	Fixed
Focal Length	4mm/4mm
Lens Mount	M12
Aperture Range	F1.0/F1.0
Field of View	(H)81.8°;(V)44.9°;(D)94.9°
DORI Distance	Detect: 57.14m Observe:22.68m Recognize:11.43m Identify:5.71m
Illuminator	
IR LEDs	N/A
IR Distance	N/A
Wavelength	N/A
White LEDs	4+4
Whitelight Distance	20m
Compression Standard	
Video Compression	S+265/H265
Video Bit Rate	Fixde Lens:32k~4Mbps Pan & Tilt Lens:32k~4Mbps
Audio Compression	G.711A/G.711U
Audio Sampling Rate	8kHz/16kHz
Image	
Max. Resolution	2304x1296@15fps
Main Stream	Fixde Lens: PAL:15fps(2304x1296) NTSC:15fps(2304x1296) Pan & Tilt Lens: PAL:15fps(2304x1296) NTSC:15fps(2304x1296)
Sub Stream	Fixde Lens: PAL:15fps(2304x1296) NTSC:15fps(2304x1296) Pan & Tilt Lens: PAL:15fps(2304x1296) NTSC:15fps(2304x1296)
Third Stream	N/A
BLC	N/A
HLC	N/A
AGC	Yes

Tiandy

3D DNR	Yes
White Balance	Auto
ROI	N/A
Corridor mode	N/A
EIS	N/A
OSD	16*16/32*32/48*48
Picture Overlay	N/A
Privacy Mask	N/A
Defog	N/A
Feature	
Alarm Trigger	Disk Full;Disk R/W Error
Video Analytics	N/A
Rules of behavior analyse in 1 scene	N/A
Early Warning(EW)	N/A
Face Mode	N/A
Face Detection Performance	N/A
Linkage Method	trigger sound;trigger warmlight;trigger recording;trigger capture
Network	
ANR	N/A
Protocols	TCP/IP;UDP;ICMP;DHCP;DNS;NTP;IPv4;SSH;Unicast
System Compatibility	P2P
Remote Connection	≤2
Client	N/A
Moblie Client	EasyLive Plus
Web	N/A
Interface	
Communication Interface	N/A
Audio I/O	N/A
Alarm I/O	N/A
Built-In Mic	Yes
Built-In Speaker	Yes
Reset Button	Yes
On-board storage	Support microSD/microSDHC/microSDXC card, up to 256 GB
Additional interfaces	N/A
General	
Web Client Language	N/A
Operating Temperature	-10°C~50°C(No turning on the light)
Operating Humidity	Humidity 95% or less (no condensation)
Storage Temperature	-10°C~50°C(No turning on the light)
Storage Humidity	Humidity 95% or less (no condensation)
Power Supply	DC5V 3A
Protection	Surge500V;ESD6000V;IP65
Boundary Dimensions	183(L)105(W)102(H)mm
Package Dimensions	265(L)195(W)285(H)mm
GrossWeight	1.66kg
NetWeight	0.9kg

Tiandy

DIMENSIONS (Unit: mm)

